



## Product: Permastic Adhesive

**MSDS Date:** 9-26-11  
**Product Name:** Permastic Adhesive  
**Manufacturer:** DERBIGUM Americas, Inc.

## I. Product and Company Description

DERBIGUM Americas, Inc.  
4821 Chelsea Ave.  
Kansas City, MO 64130

**Emergency Phone Number:**  
(800) 424-9300 (CHEMTREC)

**For Product Information:**  
(800) 727-9872

**Product Description:**  
Mixture of asphalt, naphtha solvent, filler, and cellulose fibers

## II. Chemical Composition

<u>Component</u>	<u>CAS NO.</u>	<u>% by Weight</u>
Petroleum Asphalt	8052-42-4	50 ± 5
Fillers & fibers	mixture	30 ± 5
Aliphatic Petroleum Distillate	64742-88-7	15 ± 5
Additives	mixture	1 ± 0.5

Note: The above components and their percentages are provided for health and safety purposes, ONLY. This document should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

## III. Hazards Identification

### EMERGENCY OVERVIEW:

Appearance and odor: Black, thick liquid with an aliphatic hydrocarbon odor.

WARNING STATEMENTS: COMBUSTIBLE, HARMFUL OR FATAL IF SWALLOWED, SKIN IRRITANT

### POTENTIAL HEALTH EFFECTS:

Likely Routes of Exposure:

**EYE CONTACT:** Conjunctivitis, irritation, tearing burning.  
**SKIN CONTACT:** Irritation or inflammation. Allergic skin reactions may occur. Dermatitis.  
**INHALATION:** Irritation to mucous membranes and respiratory tract, nausea, dizziness, and headache.  
**INGESTION:** Unlikely route of entry. 3-5 oz. may be fatal.

Refer to Section 11 for toxicological information.



**Product: Permastic Adhesive**

## IV. First Aid Measures

- IF IN EYES:** Immediately flush with large amounts of potable water. Eye lids should be held away the eyeball to ensure thorough rinsing. Get medical attention if irritation persists.
- IF ON SKIN:** Remove contaminated clothing and wash with soap and water.
- IF INHALED:** Remove affected person from source of exposure. If not breathing, institute cardiopulmonary resuscitation (CPR). If breathing is difficult, give oxygen. Get medical attention.
- IF INGESTED:** Do not induce vomiting – aspiration hazard. If spontaneous vomiting occurs, monitor for breathing difficulty. Get immediate medical attention. 3-5 ounces may be fatal.

## V. Fire Fighting Measures

- |  |   |
|--|---|
| <b>FLASH POINT:</b>                        | > 105 °F Tag Closed Cup LEL – 0.9% UEL 6.0%   |
| <b>HAZARDOUS PRODUCTS OF COMBUSTIONS:</b>  | H <sub>2</sub> S, CO, CO <sub>2</sub> and SOX   |
| <b>EXTINGUISHING MEDIA:</b>                | Foam CO <sub>2</sub> or dry chemical extinguishers.<br>Use bunker gear and self contained breathing apparatus. There is a potential for containers to rupture violently in fires. Vapors from product may explode if ignited in a confined space. |
| <b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b> | Do not direct water on substance. Water and foam may cause frothing. Treat as a fuel fire.  |

## VI. Accidental Release Measures

If your facility or operation has an “oil or hazardous substance contingency plan”, activate the procedure. Take immediate steps to stop and contain the spill.

Shut off all sources of ignition.

- Keep people away.
- Eliminate sources of ignition.
- Recover free product, add limestone, earth, or other suitable absorbents.
- Minimize skin contact and avoid breathing vapors.
- Ventilate confined spaces.
- Keep product out of sewers and waterways by diking or impounding.
- Advise authorities if product has entered sewers, waterways or extensive land areas.
- Assure conformity with all applicable government regulations.
- Dispose of in an approved facility, see Section 13, Disposal Considerations.



**Product: Permastic Adhesive**

## VII. Handling and Storage

**HANDLING:** Keep containers cool, dry and away from sources of ignition. Use this product with adequate ventilation. Material is COMBUSTIBLE. Material requires electrical grounding during material transfer process to prevent fire or explosion risk from static accumulation and discharge. All electrical equipment in storage and handling areas should be installed per NFPA requirements.

**STORAGE:** Keep containers tightly closed when not in use. DO NOT STORE NEAR HEAT, SPARKS, FLAME, OTHER SOURCES OF IGNITION OR STRONG OXIDIZERS.

## VIII. Exposure Controls/Personal Protection

**EYE PROTECTION:** Wear chemical splash goggles (ANSI Z87.1) or safety glasses when working with or transferring this product. DO NOT WEAR CONTACT LENSES IN THE PRESENCE OF THIS MATERIAL UNLESS SPLASH GOGGLES ARE WORN.

**SKIN PROTECTION:** Use chemical resistant gloves, to avoid prolonged or repeated skin contact.

**RESPIRATORY PROTECTION:** Use NIOSH or MSHA approved respiratory protective equipment when airborne exposure limits are exceeded.

**VENTILATION:** Ventilation may be used to reduce airborne concentrations. If ventilation can not reduce airborne concentrations below acceptable limits, appropriate respiratory protection should be used.

AIRBORNE EXPOSURE LIMITS:	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Aliphatic Petroleum Distillate	100 ppm	100 ppm

*Note: All pigments, fillers, fibers and extenders in this product are totally encapsulated and do not pose a respirable dust hazard during installation and use of this product.*

Components referred to herein, may be regulated by specific Canadian provincial legislation. Please refer to exposure limits legislated for the province in which the substance will be use.



## Material Safety Data Sheet

**Product: Permastic Adhesive**

### IX. Physical and Chemical Properties

CHEMICAL FORMULA: Not applicable, mixture  
APPEARANCE: Black thick liquid, approximately 50,000 cps @ 77 °F  
ODOR: Aliphatic hydrocarbon odor  
pH: Not applicable  
MELTING POINT (°F): Not applicable  
DENSITY (lb./gal): Approximately 10.0 (heavier than water)  
SOLUBILITY IN WATER: Less than 0.5%

**NOTE:** *These physical data are typical values based on material testing, but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.*

### X. Stability and Reactivity

STABILITY: Stable  
MATERIALS TO AVOID: Strong oxidizers, heat, spark or open flame  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, hydrogen sulfide and sulfur dioxide  
HAZARDOUS POLYMERIZATION: Will not occur

### XI. Toxicological Information

Oral – rat LD50 (mg/kg):	>5000 mg/kg	Based upon aliphatic petroleum distillate
Dermal – rabbit LD50 (mg/kg):	>3000 mg/kg	Based upon aliphatic petroleum distillate
Eye Irritation – rabbit:		No data available
Skin Irritation – rabbit (24-hr exposure):		No data available

### XII. Ecological Information

This product may cause adverse environmental effects if used improperly or release to the environment through a spill. Employ best management practices to prevent this material from entering storm sewer systems, waterways or otherwise impacting plant and animal species.



**Product: Permastic Adhesive**

**XIII. Disposal Considerations**

Dispose of in an environmentally safe manner and in accordance with governmental regulations. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. For work on tanks, refer to OSHA regulation ANSI Z49.1 and other governmental and industrial references pertaining to cleaning, repairing, welding or other contemplated operations.

**This is "RCRA" regulated hazardous waste [D001 Ignitable per 40 CFR 260.21] and must be disposed in a permitted facility. Containers are hazardous waste if not emptied completely (less than 1 inch of residue).**

The transportation, storage, treatment and dispose of this waste must be conducted in accordance with all applicable federal, state and local regulations.

**XIV. Transport Information**

The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transportation.

US DOT:	Non-bulk packages (< 119 gl capacity) are exempt from DOT HAZMAT requirements Bulk packages @ less than 105 °F (119 gl or greater) Tars, liquid, 3, UN1999, PG II Bulk packages above 105 °F (119 gl or greater) Elevated Temperature Liquid, Flammable, n.o.s., 3, UN3256, PG III
CANADIAN TDG:	Tars, liquid, 3, UN1999, PG II

**XV. Regulatory Information**

TSCA INVENTORY:	Components are listed
DSL INVENTORY:	Components are listed
WHMIS CLASSIFICATION:	Class B, Division 2
SARA HAZARD NOTIFICATION:	
Hazardous Categories Under Title III Rules (40 CFR 370):	
Section 302 Extremely Hazardous Substances:	Not Required
Section 313 Toxic Chemical(s):	Not Required

CERCLA REPORTABLE QUANTITY:	<u>Component</u>	<u>% by Wt.</u>
-----------------------------	------------------	-----------------

CA Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects, and/or other reproductive harm.

Refer to Section 11 for OSHA/HPA Hazardous Chemical(s) and Section 13 for RCRA classification.



**DERBIGUM®**  
MAKING BUILDINGS SMART

## Material Safety Data Sheet

**Product: Permastic Adhesive**

### XVI. Other Information

This material has been defined as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

	Health	Fire	Reactivity	Additional Information
Suggested NFPA1 Rating	1	2	0	
Suggested HMIS1 Rating	1	2	0	
Reason for revision: Solvent change & updated hazard information			Supersedes MSDS Dated: May 25, 2010	

The information and recommendations contained herein are to the best of DERBIGUM Americas' knowledge and belief, accurate and reliable as of the date issued. DERBIGUM Americas does not warrant or guarantee their accuracy or reliability, and DERBIGUM Americas shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the users consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the users responsibility to make certain that it is relying upon the most recent, updated, information and recommendations available from DERBIGUM Americas.

The Environmental Information included, as well as the Hazardous Material Identification System (HMIS) and National Fire Protection Association (NFPA) ratings, have been included by DERBIGUM Americas in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with DERBIGUM Americas' interpretation of the available data.

#### For Other Product Information Contact:

DERBIGUM Americas, Inc  
4821 Chelsea Ave.  
Kansas City, MO 64130

Telephone: 800-727-9872  
Fax: 816-921-5007